



425 CFM (Medium Pressure)



Portable Air Compressor

425CFM at 150 PSIG-200 L/S at 10 BAR

SPECIFICATIONS, WEIGHTS AND DIMENSIONS—SULLAIR 425H PORTABLE COMPRESSOR

Delivery @ Rated Pressure	Rated Pressure psig bar	Pressure Range psig bar	Designated Model	Weight* (wet) lbs kg	Weight* (dry) lbs kg	Length (drawbar) in mm	Length (canopy) in mm	Width in mm	Height in mm	Track Width in mm	Tire Size (load range)
425 cfm 200 L/S 12.0 m ³ /min	150 10	80–150 5.5–10	2-Wheel	4440 2014	4050 1837	156.1 3966	98.8 2510	77.2 1960	74 1880	67.5 1715	H78 X 15 ST (D)
			Less Running Gear	4195 1903	3805 1726	– –	98.8 2510	59.3 1506	63.6 1616	– –	– –
Engine Make	Engine Type	Engine Model	Displacement cu in cc	Cylinders	Bore and Stroke in mm	Rated Speed rpm	Rated Power hp kW				
John Deere (Tier 3 Emission Compliant)	Diesel	4045HF285	275 4507	4	4.19 X 5.00 106 X 127	2200	140 104				



1300 WE HIRE

www.premiairhire.com.au